

LINEAR SOLENOID

Model 1104




The model 1104 miniature linear solenoid is designed to operate at high ambient temperatures. Winding wire can withstand temperatures up to 200°C. The casing is painted black to radiate extra heat to keep the internal parts cool.

Supplied with 0.05 mm thick brass spacer to reduce residual magnetic field.

● **SPECIFICATIONS:**

Electrical impedance . . . 90 Ω ±5% AT 25⁰ C

Duty cycle




Holding Force 400 gr. minimum for 0.05mm gap
(ambient temp of 50°C, and duty cycle as above)

Operating

- temperature range** -20°C to +150°C
- Shock survival** 500 g for 11msec
- Vibration tolerance** . . . 20 g up to 2 kHz
- Coil – body insulation** . . >500 MΩ under 500V
- Dimensions** ø 10.6 x 27 mm
- Cable** # 1528 BRIM, 500 mm long
- Plunger screws** S.S.S. #2-56 x 3/32
- Weight** 14 grams
- Color** Black

● **DIMENSIONS (mm):**



Rev. E

© Singer Instruments & Control Ltd., 2003

WWW.SINGER-INSTRUMENTS.COM

Information furnished by Singer Instruments & Control is believed to be accurate and reliable. However, no responsibility is assumed by Singer Instruments & Control for its use, nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Singer Instruments & Control Ltd.

Singer Instruments & Control Ltd.

3 Yozma St., Tirat Carmel 39032, ISRAEL
yuval@singer-instruments.com

Tel: 972-4-857-8880
Fax: 972-4-857-8881

540 East Main St., Branford, CT 06405, USA
fred@singer-instruments.com

Tel: 203-481-7278
Fax: 203-488-7190

